

ATF D III H

Mineral ATF oil

This is a mineral lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

Applications:

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

Performance Level

Dexron IID/II E/IIIF/IIIG/IIIH
 MB 236.1/236.5/236.6/236.7/236.9
 Ford Mercon/M2C138-CJ/166-H
 MAN 339 Typ Z1/V1
 Allison C4/TES-389
 Cat TO-2
 Voith 55.6335 (G607)
 Volvo 97341
 ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C



Features

Frictional properties: smooth shift performance.
 Anti-wear protection: extended transmission life.
 Extended oil life: excellent thermal and oxidation stability.

Specifications:

Density at 15 °C, kg/l	0,855
Viscosity 40 °C, mm ² /s	33,9
Viscosity 100 °C, mm ² /s	7,1
Viscosity Index	179
Flash Point COC, °C	196
Pour Point, °C	-45
Color	RED