

Product Information AREOL NS-A.10.15
Trans Truck 10W-40

AREOL
PREMIUM QUALITY.
SMART PRICE

Application:

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent "bore polishing" (=cylinder-wear) in diesel engines. This product is suitable for application in Euro 4 and Euro 5 engines.

Performance Level

ACEA A3/B4, E7
API CI-4/SL
Cat ECF-1-a/ECF-2
Cummins CES 20077/20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
Mack EO-N
MAN M 3275
MB 228.3
MTU Type 2
Renault VI RLD-2
Volvo VDS-3



Typicals:

Density at 15 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	4910
Viscosity 40 °C, mm ² /s	87,70
Viscosity 100 °C, mm ² /s	13,70
Viscosity Index	159
Flash Point COC, °C	222
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.