

Description:

An economical, universal fuel-saving motor oil developed using the latest technology based on specially selected synthetic base oils and a well-balanced set of advanced additives to provide the following properties:

- reduced fuel consumption,
- medium sulfate ash content,
- suitable for modern catalysts,
- very fast cold start,
- reliable lubricating film at high temperatures,
- extended oil change intervals,
- excellent detergency and dispersancy,
- effective protection against wear, corrosion, and foaming.

Application:

Universal fuel-saving motor oil specially formulated for turbocharged or naturally aspirated gasoline and diesel engines in passenger cars and delivery vans with extended oil change intervals. The oil also helps prolong the service life of diesel particulate filters. Thanks to its special formulation, the product meets the requirements of VW 504.00/507.00, also known as VW Longlife III.

Approvals and Specifications:

ACEA C2/C3

API SN/CF

VW 504.00/507.00

BMW Long Life -04

Porsche C30

MB 229.31/229.51/229.52

Fiat 955535.GS1

Fiat 955535.DS1



Density at 15°C, kg/l	0,842
Viscosity at -35°C, mPa·s	5750
Viscosity at 40°C, mm ² /s	64.00
Viscosity at 100°C, mm ² /s	12.00
Viscosity index	178
Cleveland flash point, °C,	195
Pour point, °C	-51
Total base number, mg KOH/g	8.3
Sulfated ash, %	0.78

The listed typical physicochemical characteristics are for reference only, meet approval standards, and are not mandatory technical conditions for production and sale. Due to ongoing product research and development, the information contained herein may be changed without notice